

MVD Signals

Jan Boissevain
21 July, 1997

PHENIX Note #310
PHENIX-MVD-97-27

MCM Output Cable Signals

• Power & Ground	15	
• MCM Temperature Monitor		1
• Discriminator Sum Output	2	
• Control Signals	9	
• Serial Link	6	
• Xilinx Program	1	
• Silicon Detector Bias	2	
• Spy Channels	2	
• PECL Clock for ADC		2
• LVDS Output Data	3	
• Spares	5	
		48 Total

Power/Communication Circuit Board Signals

• Power & Ground	42	
• MCM Temperature Monitors	6	
• Discriminator Sum Outputs	12	
• Control Signals	9	
• Serial Links	11	
• Xilinx Program	6	
• Silicon Detector Bias	12	
• Spy Channels	12	
• PECL Clock for ADCs	2	
• Output Data	36	
• Spares	12	
		160 Total

Power/Control Circuit Board Signals (inner central detectors) & Daughter Board Signals (pad detectors)

MCM Output Cable Connectors (2ea Elco 24 contact .5mm pitch surface mount horizontal ZIF, 0.4 amp, model # 08-6212-024-001-000)

MCM Out Connector 1 “Analog”

1. silicon bias
2. silicon bias return (tied to TGV preamp +5V Analog)
3. +5 volts analog, TGV preamp
4. spare
5. discriminator sum output
6. discriminator sum return
7. spare
8. +5 volts, analog: discriminator (requires capacitor)
9. +5 volts, analog, AMU, current sum op-amp
10. - 5 volts, analog, current sum op-amp
11. +2.5 volts, analog, Vmid (reference)
12. analog ground, comparator
13. analog ground, TGV, AMU, current sum op-amp
14. mcm temperature sensor output
15. spare
16. preamp output (spy channel)
17. AMU output (spy channel)
18. serial enable SER.EN
19. global serial enable GEN (enables SDOUT - used w/ SER. EN)
20. serial clock SCLK (XCLK)
21. serial data in SDIN (XDIN)
22. serial data out SDOUT (xilinx done when PROG asserted)
23. serial latch SLATCH
24. xilinx program PROG

MCM Out Connector 2 “Digital”

1.	+5 volts, digital, heap manager & ADC		
2.	+5 volts, digital, heap manager & ADC		
3.	digital ground, heap manager & ADC		
4.	digital ground, heap manager & ADC		
5.	spare		
6.	mode bit 0	Run/Stop	
7.	mode bit 1	Reset	Group
8.	mode bit 2	Reset	Group
9.	mode bit 3	Other	Group
10.	mode bit 4	Other	Group
11.	mode bit 5	Other	Group
12.	lvl 1 accept		
13.	Digital Ground		
14.	MCM data out clock	40 Mhz (4X Beam Clock)	
15.	Digital Ground		
16.	MCM data out 1	40 Mbit/sec serial data link #1	output data links
17.	Digital Ground		
18.	MCM out 2	40 Mbit/sec serial data link #2	
19.	Digital Ground		
20.	9.5 MHz beam clock		
21.	38 MHz clock	(4X Beam Clock)	
22.	spare		
23.	PECL differential clock	(required for ADC)	
24.	PECL differential clock	(required for ADC)	

Note: 40 Mbit/sec data links plus clock go to LVDS chips which are mounted on the Power/Communication circuit board (or Daughter board).

**Mother Board Signal 160 contact (2 x 80)
0.5 amp. current capacity**

- | | |
|--------------------------------|-----------------------------------|
| 1. mode bit 0 | 2. mode bit 1 |
| 3. mode bit 2 | 4. mode bit 3 |
| 5. mode bit 4 | 6. mode bit 5 |
| 7. lvl 1 accept | 8. 9.5 MHz beam clock |
| 9. spare | 10. 38 MHz clock (4 X beam clock) |
| 11. spare | 12. spare |
| 13. PECL differential clock* | 14. PECL differential clock* |
| 15. spare | 16. spare |
| 17. MCM1 LVDS data out clock A | 18. MCM1 LVDSdata out clock B |
| 19. MCM1 LVDS data out 1 A | 20. MCM1 LVDS data out 1 B |
| 21. MCM1 LVDS data out 2 A | 22. MCM1 LVDS data out 2 B |
| 23. MCM2 LVDS data out clock A | 24. MCM2 LVDS data out clock B |
| 25. MCM2 LVDS data out 1 A | 26. MCM2 LVDS data out clock B |
| 27. MCM2 LVDS data out 2 A | 28. MCM2 LVDS data out 2 B |
| 29. MCM3 LVDS data out clock A | 30. MCM3 LVDSdata out clock B |
| 31. MCM3 LVDS data out 1 A | 32. MCM3 LVDS data out 1 B |
| 33. MCM3 LVDS data out 2 A | 34. MCM3 LVDS data out 2 B |
| 35. MCM4 LVDS data out clock A | 36. MCM4 LVDS data out clock B |
| 37. MCM4LVDS data out 1 A | 38. MCM4 LVDS data out 1 B |
| 39. MCM4 LVDS data out 2 A | 40. MCM4 LVDS data out 2 B |
| 41. MCM5 LVDS data out clock A | 42. MCM5 LVDS data out clock B |
| 43. MCM5 LVDS data out 1 A | 44. MCM5 LVDS data out 1 B |
| 45. MCM5 LVDS data out 2 A | 46. MCM5 LVDS data out 2 B |
| 47. MCM6 LVDS data out clock A | 48. MCM6 LVDS data out clock B |
| 49. MCM6 LVDS data out 1 A | 50. MCM6 LVDS data out 1 B |
| 51. MCM6 LVDS data out 2 A | 52. MCM6 LVDS data out 2 B |
| 53. mcm 1 serial enable | 54. mcm 2 serial enable |
| 55. mcm 3 serial enable | 56. mcm 4 serial enable |
| 57. mcm 5 serial enable | 58. mcm 6 serial enable |
| 59. serial clock | 60. serial data in |
| 61. serial data out | 62. serial latch |
| 63. global serial enable | 64. spare |
| 65. xilinx program mcm1 | 66. xilinx program mcm2 |
| 67. xilinx program mcm3 | 68. xilinx program mcm4 |
| 69. xilinx program mcm5 | 70. xilinx program mcm6 |
| 71. spare | 72. spare |
| 73. mcm 1 preamp output spy | 74. mcm 1 amu output spy |
| 75. mcm 2 preamp output spy | 76. mcm 2 amu output spy |
| 77. mcm 3 preamp output spy | 78. mcm 3 amu output spy |
| 79. mcm 4 preamp output spy | 80. mcm 4 amu output spy |
| 81. mcm 5 preamp output spy | 82. mcm 5 amu output spy |
| 83. mcm 6 preamp output spy | 84. mcm 6 amu output spy |
| 85. spare | 86. spare |
| 87. mcm1 discriminator sum | 88. mcm1 discriminator sum return |
| 89. mcm2 discriminator sum | 90. mcm2 discriminator sum return |
| 91. mcm3 discriminator sum | 92. mcm3 discriminator sum return |

93.	mcm4 discriminator sum	94.	mcm4 discriminator sum return
95.	mcm5 discriminator sum	96.	mcm5 discriminator sum return
97.	mcm6 discriminator sum	98.	mcm6 discriminator sum return
99.	spare	100.	spare
101.	+5 volts, digital, heap manager, mcm 1	102.	+5 volts, digital, ADC, mcm 1
103.	+5 volts, digital, heap manager, mcm 2	104.	+5 volts, digital, ADC, mcm 2
105.	+5 volts, digital, heap manager, mcm 3	106.	+5 volts, digital, ADC, mcm 3
107.	+5 volts, digital, heap manager, mcm 4	108.	+5 volts, digital, ADC, mcm 4
109.	+5 volts, digital, heap manager, mcm 5	110.	+5 volts, digital, ADC, mcm 5
111.	+5 volts, digital, heap manager, mcm 6	112.	+5 volts, digital, ADC, mcm 6
113.	digital ground, mcm1	114.	digital ground, mcm1
115.	digital ground, mcm2	116.	digital ground, mcm2
117.	digital ground, mcm3	118.	digital ground, mcm3
119.	digital ground, mcm4	120.	digital ground, mcm4
121.	digital ground, mcm5	122.	digital ground, mcm5
123.	digital ground, mcm6	124.	digital ground, mcm6
125.	+5 volts, analog, compar, mcm 1, 2	126.	+5 volts, analog, compar, mcm 3, 4
127.	+5 volts, analog, compar, mcm 5, 6	128.	+5 volts, analog, TGV, AMU, mcm 1, 2
129.	+5 volts, analog, TGV, AMU, mcm 3, 4	130.	+5 volts, analog, TGV, AMU, mcm 5, 6
131.	-5 volts, analog, discr sum amp, m1, 2	132.	-5 volts, analog, discr sum amp, m3, 4
133.	-5 volts, analog, discr sum amp, m 5, 6	134.	+2.5 volts, analog, Vmid, mcm 1, 2
135.	+2.5 volts, analog, Vmid, mcm 3, 4	136.	+2.5 volts, analog, Vmid, mcm 5, 6
137.	analog ground, comparator, mcm 1, 2	138.	analog ground, comparator, mcm 3, 4
139.	analog ground, comparator, mcm 5, 6	140.	analog ground, TGV, AMU, mcm 1, 2
141.	analog ground, TGV, AMU, mcm 3, 4	142.	analog ground, TGV, AMU, mcm 5, 6
143.	MCM1 temperature monitor	144.	MCM2 temperature monitor
145.	MCM3 temperature monitor	146.	MCM4 temperature monitor
147.	MCM5 temperature monitor	148.	MCM6 temperature monitor
149.	silicon detector 1 bias	150.	silicon detector 1 bias return
151.	silicon detector 2 bias	152.	silicon detector 2 bias return
153.	silicon detector 3 bias	154.	silicon detector 3 bias return
155.	silicon detector 4 bias	156.	silicon detector 4 bias return
157.	silicon detector 5 bias	158.	silicon detector 5 bias return
159.	silicon detector 6 bias	160.	silicon detector 6 bias return

Note:

- The daughter board servicing the pad detector mcms has the same signals as the Power/Communications Circuit Board for the central inner detector MCMs. On the daughter board, there are 2 each Samtec TFM-140-11-S-D 80 contact header connectors. The connector located at larger radius maps to the first 80 signals of the 160 contact connector. The second 80 contact connector maps to signals 81-160 of the 160 contact connector. The mating connectors on the motherboard are Samtec SFM-140-01 80 contact socket connectors.
- The discriminator sum output is not used for the outer layer strip detectors.

* Assumes PECL clock distribution on Power/Communications Circuit Board

MVD Endplate Connections

1. DC Power -

Panduit MAS-CON IDC: 10 contact, 8 amp contact rating, (.156 pitch), 18 gauge wire.
Header (MLSS156-10TA): 31.7mm x 3.7mm x 3.2mm high Right Angle Plug
(CT156F18-10): 31.7mm x 9.0mm x 19.6mm high.

For each set of 6 MCMs (corresponds to power/communications circuit board), require 10 each 18 gauge wire. The ampacity of the 18 gauge wire is 3A. 3 each +5V, 3 each digital ground, 1 each -5V, 1 each analog ground. For 7 groups of 6 MCMs, we have 70 each 18 gauge wire. Assuming 2 mm O.D. of insulated wire + 2/3 packing factor, get a cross sectional area of 328mm² (18mm x 18mm). Associated with each connector are 5 each voltage regulators with a capacity of 3 amps each. The regulator outputs are protected by Raychem PolySwitch resettable fuses. In addition, need to current limit lines to the 160 contact connector to avoid using the connector as a fuse.

Typical Power Connector Pin Assignments

1. +5V digital
2. +5V digital return
3. +5V digital
4. +5V digital return
5. +5V analog
6. +5V analog return
7. +5V analog
8. +5V analog return
9. -5V analog
10. -5V analog return

2. Silicon Bias -

Maximum of 42 silicon detectors/quadrant => 42 bias + 42 bias returns. Low current requirement (130V Max), so use shielded 25 mil pitch cable and IDC connectors. These connectors are rated for 500Vrms at sea level. Require 2 connectors, 1 ea. 50 contact connector and 1 ea. 40 contact connector. These cables go to the power distribution box.

Silicon Bias Connector 1

50 contact header:

3M 81050-660X0X

50 contact mating socket connector:

3M 82050-6006

- | | |
|----------------------------------|---|
| 1. group 1, mcm 1, silicon bias | 2. group 1, mcm 1, silicon bias return |
| 3. group 1, mcm 2, silicon bias | 4. group 1, mcm 2, silicon bias return |
| 5. group 1, mcm 3, silicon bias | 6. group 1, mcm 3, silicon bias return |
| 7. group 1, mcm 4, silicon bias | 8. group 1, mcm 4, silicon bias return |
| 9. group 1, mcm 5, silicon bias | 10. group 1, mcm 5, silicon bias return |
| 11. group 1, mcm 6, silicon bias | 12. group 1, mcm 6, silicon bias return |
| 13. group 2, mcm 1, silicon bias | 14. group 2, mcm 1, silicon bias return |
| 15. group 2, mcm 2, silicon bias | 16. group 2, mcm 2, silicon bias return |
| 17. group 2, mcm 3, silicon bias | 18. group 2, mcm 3, silicon bias return |
| 19. group 2, mcm 4, silicon bias | 20. group 2, mcm 4, silicon bias return |
| 21. group 2, mcm 5, silicon bias | 22. group 2, mcm 5, silicon bias return |
| 23. group 2, mcm 6, silicon bias | 24. group 2, mcm 6, silicon bias return |
| 25. group 3, mcm 1, silicon bias | 26. group 3, mcm 1, silicon bias return |
| 27. group 3, mcm 2, silicon bias | 28. group 3, mcm 2, silicon bias return |
| 29. group 3, mcm 3, silicon bias | 30. group 3, mcm 3, silicon bias return |
| 31. group 3, mcm 4, silicon bias | 32. group 3, mcm 4, silicon bias return |
| 33. group 3, mcm 5, silicon bias | 34. group 3, mcm 5, silicon bias return |
| 35. group 3, mcm 6, silicon bias | 36. group 3, mcm 6, silicon bias return |
| 37. group 4, mcm 1, silicon bias | 38. group 4, mcm 1, silicon bias return |
| 39. group 4, mcm 2, silicon bias | 40. group 4, mcm 2, silicon bias return |
| 41. group 4, mcm 3, silicon bias | 42. group 4, mcm 3, silicon bias return |
| 43. group 4, mcm 4, silicon bias | 44. group 4, mcm 4, silicon bias return |
| 45. group 4, mcm 5, silicon bias | 46. group 4, mcm 5, silicon bias return |
| 47. group 4, mcm 6, silicon bias | 48. group 4, mcm 6, silicon bias return |
| 49. spare | 50. spare |

Silicon Bias Connector 2

40 contact header:

40 contact mating socket connector:

3M 81040-660X0X

3M 82040-6006

- | | |
|----------------------------------|---|
| 1. group 5, mcm 1, silicon bias | 2. group 5, mcm 1, silicon bias return |
| 3. group 5, mcm 2, silicon bias | 4. group 5, mcm 2, silicon bias return |
| 5. group 5, mcm 3, silicon bias | 6. group 5, mcm 3, silicon bias return |
| 7. group 5, mcm 4, silicon bias | 8. group 5, mcm 4, silicon bias return |
| 9. group 5, mcm 5, silicon bias | 10. group 5, mcm 5, silicon bias return |
| 11. group 5, mcm 6, silicon bias | 12. group 5, mcm 6, silicon bias return |
| 13. group 6, mcm 1, silicon bias | 14. group 6, mcm 1, silicon bias return |
| 15. group 6, mcm 2, silicon bias | 16. group 6, mcm 2, silicon bias return |
| 17. group 6, mcm 3, silicon bias | 18. group 6, mcm 3, silicon bias return |
| 19. group 6, mcm 4, silicon bias | 20. group 6, mcm 4, silicon bias return |
| 21. group 6, mcm 5, silicon bias | 22. group 6, mcm 5, silicon bias return |
| 23. group 6, mcm 6, silicon bias | 24. group 6, mcm 6, silicon bias return |
| 25. group 7, mcm 1, silicon bias | 26. group 7, mcm 1, silicon bias return |
| 27. group 7, mcm 2, silicon bias | 28. group 7, mcm 2, silicon bias return |
| 29. group 7, mcm 3, silicon bias | 30. group 7, mcm 3, silicon bias return |
| 31. group 7, mcm 4, silicon bias | 32. group 7, mcm 4, silicon bias return |
| 33. group 7, mcm 5, silicon bias | 34. group 7, mcm 5, silicon bias return |
| 35. group 7, mcm 6, silicon bias | 36. group 7, mcm 6, silicon bias return |
| 37. spare | 38. spare |
| 39. spare | 40. spare |

3. Analog Sum Outputs Connector

24 each single ended signals. Assume shielded 25 mil pitch cable and a 50 contact connector.

50 contact header:

3M 81050-660X0X

50 contact mating socket connector:

3M 82050-6006

This cable goes to the trigger interface

01. group 1, mcm1, discriminator sum
03. group 1, mcm2, discriminator sum
05. group 1, mcm3, discriminator sum
07. group 1, mcm4, discriminator sum
09. group 1, mcm5, discriminator sum
11. group 1, mcm6, discriminator sum
13. group 2, mcm1, discriminator sum
15. group 2, mcm2, discriminator sum
17. group 2, mcm3, discriminator sum
19. group 2, mcm4, discriminator sum
21. group 2, mcm5, discriminator sum
23. group 2, mcm6, discriminator sum
25. group 3, mcm1, discriminator sum
27. group 3, mcm2, discriminator sum
29. group 3, mcm3, discriminator sum
31. group 3, mcm4, discriminator sum
33. group 3, mcm5, discriminator sum
35. group 3, mcm6, discriminator sum
37. group 7, mcm1, discriminator sum
39. group 7, mcm2, discriminator sum
41. group 7, mcm3, discriminator sum
43. group 7, mcm4, discriminator sum
45. group 7, mcm5, discriminator sum
47. group 7, mcm6, discriminator sum
49. spare

02. group 1, mcm1, discriminator sum return
04. group 1, mcm2, discriminator sum return
06. group 1, mcm3, discriminator sum return
08. group 1, mcm4, discriminator sum return
10. group 1, mcm5, discriminator sum return
12. group 1, mcm6, discriminator sum return
14. group 2, mcm1, discriminator sum return
16. group 2, mcm2, discriminator sum return
18. group 2, mcm3, discriminator sum return
20. group 2, mcm4, discriminator sum return
22. group 2, mcm5, discriminator sum return
24. group 2, mcm6, discriminator sum return
26. group 3, mcm1, discriminator sum return
28. group 3, mcm2, discriminator sum return
30. group 3, mcm3, discriminator sum return
32. group 3, mcm4, discriminator sum return
34. group 3, mcm5, discriminator sum return
36. group 3, mcm6, discriminator sum return
38. group 7, mcm1, discriminator sum return
40. group 7, mcm2, discriminator sum return
42. group 7, mcm3, discriminator sum return
44. group 7, mcm4, discriminator sum return
46. group 7, mcm5, discriminator sum return
48. group 7, mcm 6, discriminator sum return
50. spare

4. Timing/Control Connectors

7 each 40 contact connectors

40 contact header:

3M 81040-660X0X

40 contact mating socket connector:

3M 82040-6006

1. mode bit 0	2. digital ground
3. mode bit 1	4. digital ground
5. mode bit 2	6. digital ground
7. mode bit 3	8. digital ground
9. mode bit 4	10. digital ground
11. mode bit 5	12. digital ground
13. level 1 accept	14. digital ground
15. 9.5 MHz beam clock	16. digital ground
17. 38 Mhz (4 X beam clock)	18. digital ground
19. serial clock	20. digital ground
21. serial data in	22. digital ground
23. serial data out	24. digital ground
25. serial latch	26. digital ground
27. mcm 1 serial enable	28. mcm 2 serial enable
29. mcm3 serial enable	30. mcm 4 serial enable
31. mcm 5 serial enable	32. mcm 6 serial enable
33. global serial enable	34. digital ground
35. xilinx program mcm1	36. xilinx program mcm2
37. xilinx program mcm3	38. xilinx program mcm4
39. xilinx program mcm5	40. xilinx program mcm6

Assume control and serial signals are single ended logic consistent with 50 ohm loads (e.g. Motorola FACT CMOS). Assume 25 mil pitch pleated foil shielded cable (3M 90101/40) with IDC connectors (3M 82040-600X .050" x .100" tripolarized wiremount mini socket) and mating headers (3M 81040-6X0C0X .050" x .100" tripolarized latch/ejector header). Require 7 each 40 contact connectors. The serial data-out signal requires a driver on the motherboard (7 signals). Header size: 7.9mm x 39.6mm x 10.3mm high

5. LVDS Outputs

7 each 36 contact connectors

36 contact header:

36 contact mating socket connector:

3M 81036-660X0X

3M 82036-6006

- | | | | |
|-----|----------------------------|-----|----------------------------|
| 01. | MCM1 LVDS data out clock A | 02. | MCM1 LVDS data out clock B |
| 03. | MCM1 LVDS data out 1 A | 04. | MCM1 LVDS data out 1 B |
| 05. | MCM1 LVDS data out 2 A | 06. | MCM1 LVDS data out 2 B |
| 07. | MCM2 LVDS data out clock A | 08. | MCM2 LVDS data out clock B |
| 09. | MCM2 LVDS data out 1 A | 10. | MCM2 LVDS data out 1 B |
| 11. | MCM2 LVDS data out 2 A | 12. | MCM2 LVDS data out 2 B |
| 13. | MCM3 LVDS data out clock A | 14. | MCM3 LVDS data out clock B |
| 15. | MCM3 LVDS data out 1 A | 16. | MCM3 LVDS data out 1 B |
| 17. | MCM3 LVDS data out 2 A | 18. | MCM3 LVDS data out 2 B |
| 19. | MCM4 LVDS data out clock A | 20. | MCM4 LVDS data out clock B |
| 21. | MCM4 LVDS data out 1 A | 22. | MCM4 LVDS data out 1 B |
| 23. | MCM4 LVDS data out 2 A | 24. | MCM4 LVDS data out 2 B |
| 25. | MCM5 LVDS data out clock A | 26. | MCM5 LVDS data out clock B |
| 27. | MCM5 LVDS data out 1 A | 28. | MCM5 LVDS data out 1 B |
| 29. | MCM5 LVDS data out 2 A | 30. | MCM5 LVDS data out 2 B |
| 31. | MCM6 LVDS data out clock A | 32. | MCM6 LVDS data out clock B |
| 33. | MCM6 LVDS data out 1 A | 34. | MCM6 LVDS data out 1 B |
| 35. | MCM6 LVDS data out 2 A | 36. | MCM6 LVDS data out 2 B |

6. Monitoring Signals

LDO output voltages (35) and MCM temperatures (42 fully populated, 34 nominal - Analog Devices TMP37) monitored on motherboard using 10 ea MAXIM 8-channel serial 12 bit ADCs. Serial control and readout from Power Distribution Box through 40 contact 3M header (81040-6X0X0X). Use 3M 90101 series 25 mil pitch pleated foil shielded cable.

Each MCM has two spy lines (AMU input and AMU output for any 1 of 256 channels) for a total of 42 spy line pairs assuming full population. Analog Devices ADG406 16 channel analog multiplexer (6 required) appears to be a candidate component. Some glue logic will be required to interface to a serial link.

40 Contact Monitor Connector Signals

1.	digital ground	2.	digital ground
3.	monitor serial clock	4.	digital ground
5.	monitor serial data in	6.	digital ground
7.	monitor serial data out	8.	digital ground
9.	monitor serial latch	10.	digital ground
11.	monitor serial enable	12.	digital ground
13.	digital ground	14.	digital ground
15.	spare	16.	spare
17.	digital ground	18.	digital ground
19.	spy serial clock	20.	digital ground
21.	spy serial data in	22.	digital ground
23.	spy serial data out	24.	digital ground
25.	spy serial latch	26.	digital ground
27.	spy serial enable	28.	digital ground
29.	spare	30.	spare
31.	analog ground	32.	analog ground
33.	amu input spy channel	34.	analog ground
35.	analog ground	36.	analog ground
37.	amu output spy channel	38.	analog ground
39.	analog ground	40.	analog ground