


1. ALL DIMENSIONS IN MILLIMETERS.
2. DIMENSIONING AND TOLERANCING PER ASME Y14.5M-1994.
3. DIMENSIONS ARE FOR FINAL PART SIZE AT ROOM TEMPERATURE (20°C, ± 1°C, 50% HUMIDITY) AFTER CURE.
4. MATERIAL: K13C2U/RS-3C GRAPHITE/CYANATE ESTER, 0.063mm CPT, LAMINATED AND CURED PER SPECIFICATION TBD. LAYUP 24 PLIES, [0,0,15,0,-15,0,15,0,-15,0,15,0]s 1.56mm TOTAL NOMINAL THICKNESS. FIBER VOLUME 59% ±3%, VOID CONTENT 2% MAX. ALTERNATE PREPREG AND CPT MAY BE USED WITH PRIOR WRITTEN APPROVAL OF HYTEC. MATERIAL CERTIFICATION SHALL BE SUPPLIED.
5. COAT ALL EXPOSED FIBERS (CUT EDGES OR RESIN STARVED AREAS) WITH HYSOL EA9396 EPOXY ADHESIVE OR OTHER HYTEC APPROVED ADHESIVE.

- 6 TEMPORARILY MARK "111-PHX-02-3701-1 REV. " (CURRENT REVISION NUMBER) AND "S/N XX" (WHERE XX IS A UNIQUE 2 DIGIT SERIAL NUMBER FOR EACH PART, STARTING WITH 01).
- 7 INDICATES CRITICAL ATTRIBUTE. MEASUREMENT SHALL BE MADE AND RECORDED.
- 8 MEASURE AND RECORD THICKNESS AT 3 LOCATIONS ALONG EACH LONG EDGE.

THIS DOCUMENT CONTAINS INFORMATION THAT IS THE PROPRIETARY PROPERTY OF HYTEC, INC.
REPRODUCTION, DISCLOSURE, OR RELEASE TO OTHERS, MANUALLY OR ELECTRONICALLY,
IS STRICTLY PROHIBITED WITHOUT THE PRIOR WRITTEN CONSENT OF HYTEC, INC.



UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS -TOLERANCES-		CAD GENERATED DRAWING. DO NOT MANUALLY UPDATE DO NOT SCALE DRAWING		HYTEC, INC	
DECIMALS X = +/- .5 .X = +/- .1 .XX = +/- .01 .XXX = +/- .001	ANGULAR .X = +/- .30° .XX = +/- .15° SURFACE FINISH = 250			TITLE PHENIX CENTRAL UPGRADE FVTX STATIONS 2,3,4 SENSOR BACKPLANE	
FINISH		Designer	Signature	DATE	
PART NO. 111-PHX-02-3701-1		Drawn	RJ Ponchione	10/2/2008	DWG. NO.
		Checked	RJ Ponchione	10/15/2009	SIZE
		Engineer	RJ Ponchione	10/2/2008	SHEET NO.
		Approved	RJ Ponchione	10/15/2009	111-PHX-02-3701 D 1 of 1
		SCALE 2:1			REVISION